

LOAD INFLATION INFORMATION FOR ST METRIC TRAILER SIZES

FOR ST TRAILER TIRES UNSED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (Lbs.) AT VARIOUS COLD INFLATION PRESSURES (psi)															
Tire Size	USAGE	25	30	35	40	45	50	55	60	65	70	75	80	95	110
ST235/85R16	DUAL	1610	1800	1930 (B) ¹⁰³	2120	2270	2400 (C) ¹¹¹	2560	2690	2830 (D) ¹¹⁷	2950	3060	3200 (E) ¹²¹	3520 (F) ¹²⁴	3860 (G) ¹²⁷
	SINGLE	1830	2040	2200 (B) ¹⁰⁸	2400	2580	2760 (C) ¹¹⁶	2910	3060	3200 (D) ¹²¹	3360	3480	3640 (E) ¹²⁵	3960 (F) ¹²⁸	4400 (G) ¹³²
ST235/80R16	DUAL	1510	1690	1820 (B) ¹⁰¹	2000	2140	2270 (C) ¹⁰⁹	2400	2510	2600 (D) ¹¹⁴	2760	2870	3000 (E) ¹¹⁹	3300 (F) ¹²²	3640 (G) ¹²⁵
	SINGLE	1720	1920	2090 (B) ¹⁰⁶	2270	2430	2600 (C) ¹¹⁴	2730	2870	3000 (D) ¹¹⁹	3140	3260	3420 (E) ¹²³	3740 (F) ¹²⁶	4080 (G) ¹²⁹

*S637T Rated Max Load conforms to 2019 Tire & Rim Association Yearbook.